

Jazzy®

600

**ALL-AROUND PERFORMANCE.
MAXIMUM STABILITY.
NO COMPROMISES.**



Jazzy® 600 shown in Candy Apple Red with beige contoured high-back seat, foot platform and Pride Flight controller.

NEW!

The new Jazzy 600 featuring Mid-Wheel 6 technology utilizes Pride's original, patented mid-wheel drive with enhanced stability. Mid-Wheel 6 technology incorporates ATX Suspension for extra stability with independent active front OMNI-Casters (nylon spherical shaped casters) that raise and lower as needed to compensate instantly for changes in the terrain. They prevent hang-ups and allow for stable transitions from one surface to the next regardless of the angle of approach.

Mid-Wheel 6 provides superb all-around performance with the added benefit of 6-wheel stability. Whether transitioning curbs, climbing rough terrain or reverse handling, Mid-Wheel 6 consistently excels.



Pride
Mobility Products Corp.

800-800-8586 (US)
888-570-1113 (Canada)
pridemobility.com



PERFORMANCE

Patented mid-wheel drive design combined with ATX Suspension (Active-Trac® with extra stability) for high level performance and maneuverability



BALANCE

Easily and smoothly climbs and transitions obstacles as large as 3"



INNOVATION

Mid-Wheel 6 technology allows active front OMNI-Casters to engage, dropping down and making initial contact with the ground, when descending curbs



MANEUVERABILITY

Compact design and tight turning radius

SPECIFICATIONS

Weight capacity:	300 lbs.
Maximum speed:	Up to 5 mph
Ground clearance:	3"
Turning radius:	19.5"
Overall length:	35.25"
Overall width:	23.5"
Wheels:	Drive: 14" pneumatic or solid
Front:	Casters: 6" solid w/ wheel sphere
Rear:	Casters: 5" solid w/ wheel sphere
Suspension:	ATX Suspension (Active-Trac® with extra stability)
Drive train:	Two-motor, mid-wheel drive
Braking system:	Intelligent braking (electronic, regenerative disc brakes)
Std. Electronics:	75 amp, Pride Flight controller
Specialty controls:	N/A
Battery charger:	On-board, 4 amp (standard)
Per-charge range:	Up to 25 miles
Battery requirements:	(2) 12 volt, deep cycle
Battery size:	NF-22
Transport weight	
Battery weight:	38 lbs. each
Base weight:	121 lbs.
Std. seat weight:	37 lbs. (medium-back)
Seat dimensions:	22" x 20" (max. contoured seating)
Warranty:	Lifetime limited warranty on frame 2-year limited warranty on electronics 18-months limited warranty on drive motors

Colors:



The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed & range vary with user weight, terrain type, battery charge, battery condition and tire pressure.

FEATURES

- OMNI-Casters (nylon spherical-shaped casters) on front and rear to prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- ATX Suspension incorporates front OMNI-Casters for enhanced performance over more varied terrain
- Easy front access to batteries
- Easily accessible side charger port
- New 75 amp, Pride Flight controller

OPTIONS

- Contoured high-back
- Solid seat pan
- Solid tires
- Lap belt
- Cup holder
- Heavy-duty dust cover
- Swing-away joystick
- Swing-away footrests
- Elevating leg rests
- Oxygen tank holder
- Cane/crutch holder
- Walker holder
- Rear basket
- Angle-adjustable footplates
- 4 amp, on-board/5 amp, off-board charger combination